

TECHNICAL SPECIFICATIONS

| | | | |
|--------------------|----------------------------------|-----------------------------|------------------------------------------------------------|
| Collection: | Art Exposure | Backing: | Enviro Bac® |
| Country of Origin: | Australia | Carpet Tiles & Planks Size: | 609.6mm x 609.6mm |
| Colours: | 6 Standard | Installation Method: | Quarter Turn, Ashlar, Brick, Monolithic, Multi-Directional |
| Yarn: | Colorstrand® Solution Dyed Nylon | Type: | Carpet Tiles and Planks |
| Surface Texture: | Patterned Textured Loop Pile | Units Per Box: | 16.00 |
| Gauge: | 47/10cm (1/12th Gauge) | m ² per box: | 5.946 |
| Product Thickness: | 7.00mm | m ² per pallet: | 118.92 |
| Pile Weight: | 576g/m ² | Pattern Repeat: | Not Applicable |


PERFORMANCE

| | |
|-----------------------|----------------------------------------------------------------------------------------------------------|
| Anti-Static: | (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity |
| Flammability: | Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for Class 2-9 buildings~ |
| Colourfast to light: | (ISO 105-B-02-1994) 6-7 |
| Light Reflectance: | Available on Request |
| Stain Resistance: | Sentry Plus Stain Protection |
| ACCS Rating: | Contract Extra Heavy Duty - 4 Star |
| Contract Guarantee: | 15 Years Available on Request* |
| Recommended Adhesive: | Refer to our GH Commercial Adhesive Guide www.ghcommercial.com |
| Soil Resistance: | Sentry Soil Protection |


SUSTAINABILITY

| | |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PVC Minimisation: | PVC Free |
| Indoor Air Quality: | Green Building Council Compliant for VOC emission rate limits |
| Product Transparency: | Declare Red List Free |
| Recycled Content: | Colorstrand® yarn contains 34% pre-consumer recycled content. Enviro Bac® backing contains a minimum of 10% pre-consumer recycled content. |
| Green Star: | Environmental Certification Scheme (ECS) Level 4 Maximum Points |
| Accreditation: | Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies. |


Academic View




924
PLATINUM



958
ECRU



569
CADET



989
CHARCOAL



853
FALLOW



959
SLATE

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions. Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request. *Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.