

Luxury Vinyl Tiles

- Ultimate durability
- Ultra matte finish
- Minimal visible pattern repeat
- Nature inspired designs
- High definition printing

www.tarkett.com.au

iD Naturals 70

 **Tarkett**

iD Naturals 70

TECHNICAL DATA

CLASSIFICATION	STANDARD	iD Naturals 70
Product Type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor covering
Classification	EN ISO 10874	23 - 34 - 43
TECHNICAL CHARACTERISTICS	STANDARD	iD Naturals 70
Total thickness	EN ISO 24346	2.5mm
Wear layer thickness	EN ISO 24340	0.70mm
Total weight	EN ISO 23997	3950g/m ²
Wear layer binder content	EN ISO 10582	Type I
Surface treatment		Tektanium™
High definition digitally printed		Yes
Bevelled edges		Yes
Installation method		Glue-Down
PERFORMANCE FOR CE MARKING REQUIREMENTS	STANDARD	iD Naturals 70
Declaration of Performance	EN 14041	0132-0085-DoP-2020-03
TECHNICAL PERFORMANCES	STANDARD	iD Naturals 70
Dimensional stability average value	EN ISO 23999	< 0.10%
Curl resistant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 9.3 kW/m ² Smoke 161 %min
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717 / 2	3 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Residual indentation	EN ISO 24343-1	≤ 0.05 mm
Thermal resistance	EN ISO 10456	0.02 m ² •K/W
Colour fastness to light	EN ISO 105-B02 (method 3 ^a)	≥6
Chemical resistance	EN ISO 26987	Excellent Resistance
Slip resistance	DIN 51130/EN 13893 AS 4586:2013	R9/R10 depending on embossing μ ≥ 0.3 P4/P5 depending on embossing
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Static electrical propensity	EN 1815	Antistatic (≤ 2kV)
Underfloor heating		Suitable - max. 27°C
SUSTAINABILITY PERFORMANCES	STANDARD	iD Naturals 70
Total VOC emissions	EN 16516	Platinum (≤ 10 µg/m ³)
Material health statement		Available
Carbon footprint (Cradle-to-Gate, EPD Modules A1-A3)		7.71 kg CO ₂ e /m ²
Recycled content		39.5%
Recyclable		Yes- installation waste
Phthalate - free		Yes
DIMENSIONS AND DESIGNS	STANDARD	iD Naturals 70
Plank		20 x 120cm - 15 planks/box = 3.60m ² 28.5 x 120cm - 11 planks/box = 3.76m ² 25 x 150cm - 10 planks/box = 3.75m ²
Tile		50 x 50cm - 15 tiles/box = 3.75m ² 50 x 100cm - 7 tiles/box = 3.50m ² 66.66 x 66.66cm - 8 tiles/box = 3.55m ² 33.33 x 66.66cm - 16 tiles/box = 3.55m ²
Number of designs available		Woods: 43 / Stones: 21

The above information is subject to modification for the benefit of further improvement. (09/22).

Tarkett's Instructions regarding installation, cleaning and maintenance should be observed

Please visit [Tarkett.com.au](https://www.tarkett.com.au) for more information

The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.



TEKTANIUM™

