

Luxury Vinyl Tiles

Affordable design

Wide range of colours

Durable

WWW.TARKETT.COM.AU



ESSENTIALS 30

 **Tarkett**

TECHNICAL DATA SHEET

Certification & classification	Standards	iD Essentials 30
Type of floor covering	EN ISO 10582	Compact Resilient Floorcovering
Classification	EN ISO 10874 (EN 685)	Domestic: 23 Commercial: 31
Technical characteristics		
Total thickness	EN ISO 24346 (EN 428)	2.0 mm
Wear layer thickness	EN ISO 24340 (EN 429)	0.30 mm
Total weight	EN ISO 23997 (EN 430)	3.4 kg/m²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342 (EN 427)	Planks 229 x 1219 mm 12 planks/box = 3.34 m²
Surface treatment (PUR)		Yes - TopClean™
Beveled edges		Yes - 4 Bevels
Technical performances		
Dimensional stability	EN ISO 23999 (EN 434)	≤ 0.25%
Curl resultant to heat	EN ISO 23999 (EN 434)	≤ 2 mm
Reaction to fire	ISO AS 9239-1	Critical radiant flux 10.2 kW/m² Smoke 78 %.min
Residual indentation	EN ISO 24343-1 (EN 433)	Required value: ≤ 0.10 mm Average measured value: 0.03 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 (EN 425)	No damage
Impact sound reduction	EN ISO 717-2 EN ISO 140-8	ΔLw = 4 dB
Thermal resistance	EN ISO 10456	0.07 m² K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987 (EN 423)	Good
Slip resistance	AS 4586:2013 DIN 51130/EN 13893	P4 R9
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 10 ¹⁰ Ω
Underfloor heating		Suitable - max. 27 °C

The above information is subject to modification for the benefit of further improvement. (09/18).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Disclaimer: Please note that products in photos are installed for creative purposes and not according to technical specifications.
Please refer to Tarkett installation instructions for guidance.

Contact: Tarkett Australia
P: 1300 851 484
E: customerservice@tarkett.com
W: www.tarkett.com.au

