

TECHNICAL SPECIFICATIONS

Country of Origin:	China	Units Per Box:	6 boards equivalent (16% Nested/ Random lengths)
Colours:	8 Standard	m ² per box:	2.166
Product Thickness:	14mm	m ² per pallet:	108.3
Backing:	Ply	Finish:	Matte Finish with light brush
Hard Flooring Size:	190mm x 1900mm	Surface:	French Oak Veneer (3mm)
Installation Method:	5G Insta Clic®	Profile:	Micro Bevel Edge
Notes:	As this is a natural product, some boxes may include 'nested' boards (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.	Substrate Layer:	Poplar
Type:	Timber Flooring	Protective Coating:	UV Cured Lacquer
Wear Layer:	3mm		

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 3.8kW/m ²
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 17% minutes
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P4 (excluding colour 300 Natural Oak P2)
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Moisture Content:	(EN 131831-1) 8-11% (+/-2%) at time of delivery
Lipping:	(EN13489) ≤0.2mm

SUSTAINABILITY

Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Corsica Oak



560
WEATHERED OAK



360
RUSTIC OAK




790
CINDER OAK



300
NATURAL OAK SMOOTH




710
ASHEN OAK



510
COASTAL OAK



180
COFFEE OAK



310
NATURAL OAK BRUSHED

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst engineered timber floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

Note: Nested/Random lengths may occur. As this is a natural products, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.