

TECHNICAL SPECIFICATIONS

Country of Origin:	Indonesia	Units Per Box:	6 boards equivalent (32% Nested/ Random lengths)
Colours:	10 Standard	m ² per box:	2.075
Product Thickness:	14.2mm	m ² per pallet:	114.125
Backing:	Ply	Finish:	Matte Finish with very light brush
Hard Flooring Size:	190mm x 1820mm	Surface:	French Oak Veneer (3.2mm)
Installation Method:	5G Insta Clic®	Profile:	Micro Bevel Edge
Notes:	As this is a natural product, some boxes may include 'nested' boards (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.	Substrate Layer:	Hevea Core
Type:	Timber Flooring	Protective Coating:	UV Cured Lacquer
Wear Layer:	3.2mm		


PERFORMANCE

Flammability:	(EN ISO 9239) CRF 5.1kW/m2
Light Reflectance:	100 - 32.84 150 - 29.84 500 - 23.70 510 - 12.83 520 - 12.11 540 - 13.80 550 - 12.00 750 - 17.84 780 - 8.17 790 - 5.26
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 11% minutes
Slip Resistance:	(AS/NZ 4586-2013) P3
Suitable for wet areas:	Kitchen, integrated laundry and powder rooms - subject to proper installation and maintenance
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Moisture Content:	(EN 131831-1) 6-8% (+/-2%) at time of delivery
Lipping:	(EN13489) ≤0.2mm


SUSTAINABILITY

Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
---------------------	---

Chateau Oak




780
MATT BLACK




550
HAVANA



790
ESPRESSO



500
ALPINE OAK



750
SILVER FINCH



540
RAFFIA



150
LIMESTONE



100
WHITE SANDS



520
AUTUMN AMBER



510
SUMMER BLONDE

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst engineered timber floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

Note: Nested/Random lengths may occur. As this is a natural products, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.