

Vista 1500



TECHNICAL SPECIFICATIONS

Country of Origin:	China	Units Per Box:	6 boards
Colours:	10 Standard	m ² per box:	1.764
Product Thickness:	8mm	m ² per pallet:	105.84
Backing:	Balancing Layer	Finish:	Matte
Hard Flooring Size:	196mm x 1500mm	Surface:	Embossed
Installation Method:	Uniclic®	Profile:	Micro Bevel
Type:	Laminate Flooring	Substrate Layer:	860kg/m ³ High Density Fibreboard

PERFORMANCE

Flammability:	(EN ISO 9239) CRF 4.8kW/m ²
Colourfast to light:	(EN ISO 105-B02, A02) 4-5 Grey Scale
Contract Guarantee:	Available on request*
Smoke Value:	(EN ISO 9239) 49% minutes
Abrasion Rating:	(EN 13329) AC4
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P1
Swelling after submersion in water:	(ISO 24336) ≤13.7%

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Vista 1500




585
MALLEE GUM



300
NATURAL



525
ALPINE BLACKBUTT



500
SAND



520
FLAX



720
COOL GREY



545
BLACKBUTT



555
SPOTTED GUM



180
HERITAGE



575
SMOKE

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst laminate products must be installed in accordance with the relevant Australian Standards and in conjunction with the Godfrey Hirst Laminate Installation Instructions.

*Terms and conditions apply to all commercial warranties - please contact your GH Commercial Account Manager.