




## Installation Method



Ashlar Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Textured Woodgrains **Colour** Antique Light Oak **Collection** Level Set Collection

## Product Specifications

Product Number	A004
Product Construction	High Performance Luxury Vinyl Plank
Wear Layer Thickness	22 MIL
Total Thickness (Metric)	4.5 mm
Classification	EN 651 Class 42 (light industrial general) EN 651 Class 33 (heavy contract)
Acoustic Impact Noise Reduction	ISO 140.8 $\Delta L_w = 16$ dB
Finish	CERAMOR+™ UV Stabilized Ceramic Bead Coating (Australia Only)
Nominal Dimensions	25cm x 100cm

## Performance Specifications

Critical Heat Flux	AS ISO 9239-1 >7kW/m <sup>2</sup>
Smoke Rate	AS ISO 9239-1 <750%.min
Size & Squareness	ISO 24342 < 400 mm < 0.25 mm ISO 24342 > 400 mm < 0.35 mm
Dimensional Stability	ISO 23999 <0.25%
Thickness	4.5 mm
Resistance to Light	ISO 105-B02 $\geq 6$
Resistance to Heat	ASTM F1514 $\Delta E < 8$ avg Max
Resistance to Chemicals	EN-ISO 26987 Passes
Reaction to Fire	EN ISO 13501-1 Class BFI-S1
VOC Test	ISO 10580 Pass
Flexibility	ISO 24344 Method A Pass
Static Load	ASTM F970 $\leq 0.005$ " with 1500 psi
Castor chair	ISO 4918 Pass
Thermal Conductivity	EN 12667 0.16 W/mK
Static Electrical	EN 1815 <2kV
Slip Resistance	AS 4586:2013 R10, P3

## Environmental Specifications

Ingredients and Life Cycle Impacts	Environmental Product Declaration
Sustainability Assessment	NSF/ANSI 332, Meets Certification Guidelines
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR
End of Life	Fully Recyclable LVT to Carpet Tile Backing Recycling
Full Life Cycle Carbon	Certified Carbon Neutral Floors™

## Technical Information

Installation	<a href="#">See Interface LVT Installation Guidelines online</a>
Maintenance	<a href="#">See Interface LVT Installation Guidelines online</a>
Reclamation	<a href="#">View details on our ReEntry™ Program</a>
Warranty	<a href="#">15 Year Standard LVT Product Warranty</a>