




Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Flashplay **Colour** Glisten **Backing** GlasBac™

Product Specifications

Yarn System	100% Solution Dyed Nylon
Standard Backing	GlasBac™
Size	50cm x 50cm

More Product Specifications

Total Thickness	5.5 mm ±0.5 mm
Gauge - Ends per 10 cm	47.2 ends/10cm

Performance Specifications

Castor Chair Rating	BS-EN 985 r ≥ 2.4
Light Fastness	AS2001 1.4.21 ≥ 4
Dimensional Stability	ISO/PAS 17984 < 0.2%

Environmental Specifications

Disclosure of Product Ingredients	GlasBac™
Total Recycled Content	14.78 %
Pre-Consumer (Total)	12.81 %
Post-Consumer (Total)	1.97 %
Embodied Carbon (Cradle to Gate)	4.89 kg CO ₂ eq./m ²

Technical Information

Installation	View recommended Interface Installation Guidelines online
Maintenance	View recommended Interface Maintenance guidelines online
Warranty	15 Year Standard Warranty
Manufacturing Location	ISO 9001, 14001 & 45001 Certified facilities in Minto, Australia

Certifications

