



**Installation Method**



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Textured Woodgrains    **Colour** Antique Light Oak    **Collection** Level Set Collection

**Product Specifications**

Product Number	A004
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	CERAMOR+™ UV Stabilized Ceramic Bead Coating
Wear Layer Thickness	0.55 mm
Total Thickness	ISO 24346 Average value + 0.20mm
Size	25cm x 1m

**Performance Specifications**

Castor Chair Rating	ISO 4918 Pass
Flammability	EN ISO 13501-1 Class BFI-S1
Dimensional Stability	ISO 23999 <0.25%
Curling	(ISO 23999) ≤ 2
Flexibility	ISO 24344 Method A Pass
Residual Indentation	ISO 24343-1
Chemical Resistance	EN-ISO 26987 Passes

**Environmental Specifications**

Environmental Product Declaration	<a href="#">Download EPD</a>
Total Recycled Content	39 %
Indoor Air Quality	FloorScore® SCS-FS-04366
Embodied Carbon (Cradle to Gate)	9.2 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life Options	Fully Recyclable LVT to Carpet Tile Backing Recycling
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers

**Technical Information**

Installation	See Interface LVT Installation Guidelines online
Maintenance	LVT Maintenance
Warranty	15 Year Standard LVT Product Warranty

**Certifications**
