


**Installation Method**

Quarter turn Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Employ Loop **Colour** Lavender **Collection** Employ Collection **Backing** GlasBac™

Product Specifications

Product Construction	Tufted Level Loop Pile
Yarn System	100% Solution Dyed Nylon
Standard Backing	GlasBac™
Size	50cm x 50cm

More Product Specifications

Pile Yarn Weight	518 g/m ² ± 5%
Total Weight	3,734 g/m ² ± 5%
Total Thickness	4.5 mm ±0.5 mm
Gauge - Ends per 10 cm	39.4 ends/10cm
Tufts per m ²	200940 /m ² ±5%

Performance Specifications

UPEC Classification	U3 P3 E1 C0
Castor Chair Rating	BS-EN 985 r ≥ 2.4
Light Fastness	AS2001 1.4.21 ≥ 4
Dimensional Stability	ISO/PAS 17984 < 0.2%
Rating of Sound Absorption (aw) EN ISO 11654	0.15

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	GlasBac™
Total Recycled Content	2.67 %
Pre-Consumer (Total)	0.76 %
Post-Consumer (Total)	1.91 %
Embodied Carbon (Cradle to Gate)	5.13 kg CO ₂ eq./m ²

Technical Information

Installation	View recommended Interface Installation Guidelines online
Maintenance	Recommended Interface Maintenance Guidelines
Warranty	15 Year Standard Warranty
Manufacturing Location	ISO 9001, 14001 & 45001 Certified facilities in Minto, Australia

Certifications

DOP: 1037/127337 EN 14041:2004 Notified Body - 0493 COC 0483 - CFR - 0181 For use as floor covering in buildings	DOP: 1037/127337 EN 14041:2004 Approved Body - 8515 COC 8515/CPB/0181 For use as floor covering in buildings				
0.15	≥ 7				
 318T-016.3					