



Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Open Air 401 **Colour** Stone **Collection** Open Air Neutrals **Backing** GlasBac™

Product Specifications

Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	GlasBac™
Size	25cm x 1m

More Product Specifications

Pile Yarn Weight	610 g/m ² ± 5%
Total Weight	4,128 g/m ² ± 5%
Total Thickness	5.9 mm ±0.5 mm
Gauge - Ends per 10 cm	47.2 ends/10cm
Tufts per m ²	164,394 /m ² ±5%

Performance Specifications

Castor Chair Rating	BS-EN 985 r ≥ 2.4
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Light Fastness	AS2001 1.4.21 ≥ 4
Dimensional Stability	ISO/PAS 17984 < 0.2%
Rating of Sound Absorption (αw) EN ISO 11654	0.2

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	GlasBac™
Total Recycled Content	21.35 %
Pre-Consumer (Total)	10.12 %
Post-Consumer (Total)	11.23 %
Yarn Recycled Content	100 %
Embodied Carbon (Cradle to Gate)	5.37 kg CO ₂ eq./m ²

Technical Information

Installation	View recommended Interface Installation Guidelines online
Maintenance	View recommended Interface Maintenance guidelines online
Warranty	15 Year Standard Warranty
Manufacturing Location	ISO 9001, 14001 & 45001 Certified facilities in Minto, Australia

Certifications

 DOP: 1037/128746 EN 14041:2004 Notified Body - 0493 COC 0493 - CFR - 0181 For use as floor covering in buildings	 DOP: 1037/128746 EN 14041:2004 Approved Body - 8515 COC 8515/CFR/0181 For use as floor covering in buildings		>0,30	< 2,0 kV	0.2
≥ 7			≥2.4		