




Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Criterion Classic Woodgrains **Colour** Washed Maple

Product Specifications

Product Number	C001
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	Ceramor™ UV stabilised Ceramic Bead Coating
Wear Layer Thickness	0.55 mm
Total Thickness	ASTM F386 Passes
Size	12.5cm x 1m

Performance Specifications

Flexibility	ASTM F137 Passes
Residual Indentation	ASTM F1914 Passes
Chemical Resistance	ASTM F925 Passes

Environmental Specifications

Environmental Product Declaration	Download EPD
Total Recycled Content	39 %
Indoor Air Quality	FloorScore® SCS-FS-04366
Embodied Carbon (Cradle to Gate)	7.27 kg CO ₂ eq./m ²
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	LVT Maintenance
Warranty	10 Year Standard LVT Product Warranty

Certifications

<p>Interface European Manufacturing DC 3000 BSC Scherpenheuvel The Netherlands 020 48522222 ext 1000 EN 15348:2008 Installation: 10000</p>	<p>Interface European Manufacturing DC 3000 BSC Scherpenheuvel The Netherlands 020 48522222 ext 1000 EN 15348:2008 Installation: 10000</p>				