


Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Hearth **Colour** Gris **Collection** Earthen Forms Collection

Product Specifications

Product Number	A035
Product Construction	High Performance Luxury Vinyl Tile contains 39% Pre-Consumer Recycled Content
Finish	CERAMOR+™ UV Stabilized Ceramic Bead Coating
Wear Layer Thickness	0.55 mm
Total Thickness	ISO 24346 Average value + 0.20mm
Size	50cm x 1m

Performance Specifications

Castor Chair Rating	ISO 4918 Pass
Flammability	EN ISO 13501-1 Class BFI-S1
Light Reflectance Value (LRV-L)	64.38
Dimensional Stability	ISO 23999 <0.25%
Curling	(ISO 23999) ≤ 2
Flexibility	ISO 24344 Method A Pass
Residual Indentation	ASTM F1914 Passes
Chemical Resistance	EN-ISO 26987 Passes

Environmental Specifications

Environmental Product Declaration	Download EPD
Total Recycled Content	39 %
Indoor Air Quality	FloorScore® SCS-FS-04366
Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m ²
End of Life Options	Fully Recyclable LVT to Carpet Tile Backing Recycling
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	LVT Maintenance
Warranty	15 Year Standard LVT Product Warranty

Certifications

	<p>CE</p> <p>24</p> <p>Interface Europe Manufacturing B.V. Industrieweg 19 4472 DJ Streepland Tilburg DOPWC2024-0087 02114412264 Netherlands - 5025</p> <p>Product description: Classification: Class III (EN ISO 10076) Reaction to fire: Class B (EN ISO 10076) Resistance to fire: Class B (EN ISO 10076) Flammability: Class B (EN ISO 10076) Emission: Class B (EN ISO 10076) www.interface.com/en</p>	<p>UK</p> <p>SE</p> <p>Interface Europe Manufacturing B.V. Industrieweg 19 4472 DJ Streepland Tilburg DOPWC2024-0087 02114412264 Netherlands - 5025</p> <p>Product description: Classification: Class III (EN ISO 10076) Reaction to fire: Class B (EN ISO 10076) Resistance to fire: Class B (EN ISO 10076) Flammability: Class B (EN ISO 10076) Emission: Class B (EN ISO 10076) www.interface.com/en</p>			