


Primo SD

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Static dissipative pressed homogeneous vinyl flooring
Winder content	ISO 10581	Type I
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Surface treatment		PUR Reinforced
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	3000 g/m ²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0019-0047-DoP-2014-03
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 10.5kW/m ²
Reaction to fire	AS/ISO 9239.1	Smoke 32%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m ² ·K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0,10 mm Best measured value: 0,03 mm
Slip resistance	DIN 51130	R10
Slip Resistance	AS 4586	P3
Electrical Insulation	VDE0100, Part 600	Ri ≥ 5x10 ⁴ Ohms
Electrical resistance	EN 1081	R1 < 10 ⁸ Ω
Curl resultant to heat	EN ISO 23999	≤ 8 mm for rolls ≤ 2 mm for tiles
Castor chair	ISO 4918	Suitable
Light fastness	ISO 105-B02	≥ 6
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 %Average measured value : ≤ 0.25 % for tiles
Ease of Decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Seam Strength Average Value	EN 684	≥ 240 N/50mm
Seam Strength Individual Value	EN 684	≥ 180 N/50mm
Sustainability performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,71 kg CO ₂ eq /m ²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)
Formaldehyde emission class		E1
Dimensions and designs		
Roll	Roll 2 x 23 m	
Tile	Tile 610 x 610 mm - 16 tiles= 5.95 m ² /box - 40 boxes/pallet	
Number of designs available	8	



For Global Green Tag certificates please see the Tarkett Australia page at globalgreentag.com

The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
Suite 1, Level 3, 3 Columbia Court, Baulkham Hills NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au

