

iD Inspiration Loose Lay

Acoustic performance

Extensive colour range

4.5mm thickness for
durability

WWW.TARKETT.COM.AU

LUXURY VINYL TILES

 Tarkett

iD Inspiration Loose Lay

Technical Datasheet

Classification	Standards	iD Inspiration Loose Lay
Product Type	EN ISO 10582	Heterogeneous poly (vinyl chloride) floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
Technical Characteristics	Standards	iD Inspiration Loose Lay
Total thickness	EN ISO 24346	4.5mm
Wear layer thickness	EN ISO 24340	0.55mm
Total weight	EN ISO 23997	7500 g/m ²
Wear Layer Binder content	EN ISO 10582	Type I
Surface treatment		PUR
Bevelled edges		No
Installation method		Loose Lay
Technical Performances	Standards	iD Inspiration Loose Lay
Dimensional stability	EN ISO 23999	≤ 0.10%
Reaction to fire	EN 13501-1	Critical radiant flux 9.1 kW/m ² Smoke 172%.min
Furniture leg	EN 424	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction	EN ISO 717/2	ΔLw 8dB
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Thermal resistance	EN ISO 10456	0.04 m ² ·K/W
Colour fastness to light	EN ISO 105-B02 (method 3 ^o)	≥ 6
Chemical resistance	EN ISO 26987	High Resistance
Slip resistance	DIN 51130/EN 13893 AS 4586	R9 P2
Electrical properties	EN 1081	ca. 10 ¹¹ Ohm
Sustainability Performances	Standards	iD Inspiration Loose Lay
Phthalate		Not Detected
Total VOC emissions	EN 16516	Gold (≤ 100 µg / m ³)
Dimensions	Standards	iD Inspiration Loose Lay
Planks		229 x 1219mm - 10 planks/box = 2.79m ²

The above information is subject to modification for the benefit of further improvement. (05/25). Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please note the the products in the photos are installed for creative purposes and not according to technical specifications.

