

Acczent Excellence Compact+

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10582	Polyvinyl chloride floor coverings with foam layer
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Binder content	ISO 10582	Type I
Technical Characteristics	Norm	Tarkett Value
Wear layer thickness	EN ISO 24340	0,80 mm
Total thickness	EN ISO 24346	2,15 mm
Total weight	EN ISO 23997	2750 g/m ²
Surface treatment		TEKTANIUM™
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-103-DoP-2023-06
Reaction to fire	S/ISO 9239.1	Critical radiant flux 7.0kW/m ² Smoke 236%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN ISO 10456	0,04 m ² •K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,20 mm Average measured value: 0,03 mm
Dimensional stability	EN ISO 23999	≤ 0.40 % Average measured value : ≤ 0.10 %
Impact sound reduction - ΔLw	EN ISO 717/2	8 dB
Reduction of in-room impact noise	NF S31-074	Class B (≤ 75 dB)
Slip resistance	DIN 51130 AS 4586	R10 P4
Castor chair	EN ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	≤ 8 mm
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability Performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through Resilooop		Recyclable
Recycled content		27 %
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 μg/m ³)
Formaldehyde emission	EN 717-1	E1
GreenTag		Level A
HealthRATE		Platinum
Dimensions and Designs		
Roll		Roll 2 x 23 m
Number of designs available		93



The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.